

## MINICOLLECTOR

Mod.:

**MINIPAC III**

Capacity:

3 m<sup>3</sup>



## TECHNICAL CHARACTERISTICS CARGO BOX

<b>CAPACITY (m<sup>3</sup>):</b>	3,25
<b>DESIGN FOR:</b>	
○ CHASSIS:	4x2 & 4x4
○ DISTANCE BETWEEN AXLES (mm):	2900 TO 3450
○ CABIN:	SHORT
<b>GROSS VEHICLE WEIGHT (Tm):</b>	4,5 TO 6,5 Tm
<b>TIPPING ANGLE:</b>	84°
<b>STEEL HOPPER WITH HIGH ELASTIC LIMIT</b>	DOMEX 690
<b>THICKNESS:</b>	
○ BOTTOM (mm):	2,5
○ SIDES (mm):	2,5
○ FRONT (mm):	2,5
○ HOPPER RAMP (mm):	3
○ ROOF (mm):	2
<b>WELDING:</b>	CONTINUOUS
<b>REAR DOOR FOR MANUAL BAGGING</b>	YES
<b>SPARE WHEEL SUPPORT ON EQUIPMENT</b>	
<b>SIDE PROTECTIONS ACCORDING TO DIRECTIVE (89/297/CEE)</b>	



## ADVANTAGES

- + **REDUCED DIMENSIONS:**  
FOR COLLECTION IN NARROW PLACES
- + **HIGH COMPACTION CAPACITY:**  
FINAL DENSITY OBTAINED: 600-650 kg/m<sup>3</sup>
- + **HIGH DISCHARGE HEIGHT:**  
UNLOADING IN LARGER REFUSE COLLECTORS
- + **TIGHT SEAL:**  
DURING THE TRANSFER

**VERY IMPORTANT:** Chassis must be provided with Power Take-Off.

## TECHNICAL CHARACTERISTICS HYDRAULIC EQUIPMENT

- ✂ **PUMP (GEAR PUMP):** Q=33cm<sup>3</sup>/rev
- ✂ **DIRECT COUPLING PUMP-GEARBOX**
- ✂ **DOUBLE ACTING STABILIZING JACKS (CHROMED)**
- ✂ **DOUBLE EFFECT CYLINDERS, CHROMED, FOR:**
  - TIPPING
  - COMPACTION
  - LIFTING
- ✂ **REAR LIFT FOR CONTAINERS:**
  - STANDARD CONTAINERS (80 TO 800 l)
- ✂ **TURNS WITH BRONZE CAP AND GREASE FITTING**
- ✂ **COMPACTION PLATE TYPE "PENDULUM"**
- ✂ **PUSH BUTTON CONTROL ON BOTH SIDES**  
(FOR LIFTING, TIPPING AND COMPACTION)
- ✂ **EMERGENCY STOP DEVICE IN CABIN**

**DANIMA INGENIERIA AMBIENTAL, S.A.**

PARQUE EMPRESARIAL PRINCIPADO DE ASTURIAS, PARCELA 12 – 33417 AVILES (ASTURIAS) SPAIN

web: [www.danima.es](http://www.danima.es)

mail: [danima@danima.es](mailto:danima@danima.es)

tel: +34 985 514 450