

---

## **AUTOMATIZED TENT**

**Mod.: SPEEDCARP**

**"NIEMEYER"**

*Square 200 m<sup>2</sup>*



## **TECHNICAL CHARACTERISTICS**

<b>DESIGN:</b>	SQUARE
<b>AREA:</b>	200m <sup>2</sup>
<b>MAXIMUM INTERIOR HEIGHT:</b>	5,5m
<b>ENTRANCE HEIGHT:</b>	4,25m
<b>SUPPORTS:</b>	8 ADJUSTABLE
<b>CANVAS FIXING SYSTEM:</b>	TENKEDER
<b>(1)LIFTING SYSTEM:</b>	TELESCOPIC HYDRAULIC ARM
<b>CHASSIS:</b>	PLATAFORM CON TWIST-LOCK
<b>STANDARD CANVAS:</b>	FIREPROOF
<b>STANDARD CANVAS WEIGHT:</b>	620gr/m <sup>2</sup>
<b>STANDARD CANVAS THICKNESS:</b>	0,49 mm
<b>RESISTANCE TO TEMPERATURE:</b>	30°C/+80°C
<b>ESTIMATED ASSEMBLING TIME:</b>	45'
<b>Nº OF OPERATORS:</b>	2/3

- ✓ AUTOINSTALLATION
- ✓ QUICK ASSEMBLY
- ✓ PROFITABLE
- ✓ EASY ASSEMBLY
- ✓ INNOVATIVE
- ✓ VERSATILE

(1) The lifting system is independent from the Speedcarp tent. It is made up of: a frame with platform with twist-lock, with standard dimensions for 40'(ft) and with a telescopic system that is activated through an independent hydraulic center.

---

### **DANIMA INGENIERIA AMBIENTAL, S.A.**

PARQUE EMPRESARIAL PRINCIPADO DE ASTURIAS, PARCELA 12 – 33417 AVILES (ASTURIAS) SPAIN

web: [www.danima.es](http://www.danima.es)

mail: [danima@danima.es](mailto:danima@danima.es)

tel: +34 985 514 450