

COMPACTION CONTAINER

Mod.: STANDARD
Capacity: 40 m³

OTHER CAPACITIES:
30 m³, 34 m³ and 43 m³



TECHNICAL CHARACTERISTICS

MADE OF ONE SINGLE METALLIC PLATE:

- AVOIDING THE TRANSVERSE WELDING SEAMS
- LONGER WORKING LIFE
- SIGNIFICANT REDUCTION OF DEFORMATION RISK
- LOWER MAINTENANCE COST

CONTAINER VOLUME (m³): 40

APPROX. TARE WEIGHT (kg): 4950

THICKNESS (mm):

- BOTTOM: 4
- SIDES: 3
- ROOF: 3

LONGITUDINAL CHAMFER OF 45°:

- OPTIMUM WASTE FLOW DURING COMPACTION
- COMPLETE DISCHARGE BY GRAVITY

MADE OF STEEL S275JR ACCORDING TO UNE-EN 10025

MANIPULABLE BY HOOKLOADER DANROLL (BRAND DANIMA)

OTHER INFORMATION

INCLUDES:

- SUBFRAME FOR BEING HANDLED AND TRANSPORTED BY THE CONTAINER HOOKLOADER DANROLL
- FOUR LAMINATED STEEL ROLLERS FOR SUPPORT AND SLIDING
- REAR DOOR: SIDE OPENING (DOOR OPENING UPWARDS)
- ANTI-LEACHATES SEALING
- DOOR LOCKED BY RATCHET TENSIONER
- ALUMINIUM TOP WITH AWNING FOR THE COMPLETE CLOSING OF THE DOOR

DANIMA INGENIERIA AMBIENTAL, S.A.

PARQUE EMPRESARIAL PRINCIPADO DE ASTURIAS, PARCELA 12 – 33417 AVILES (ASTURIAS) SPAIN
web: www.danima.es mail: danima@danima.es

tel: +34 985 514 450